CHEONGWOO CFC® CO., LTD.

Slip CFC®-720P

Additive to improve levelling and slip in organic solvent system

Main component

Polyether polysiloxane surfactant

Physical & Properties

Appearance	Clear liquid
Solid content (%)	52 ± 2
Gravity (20℃)	0.85 ± 0.02
Solvent	PMA

Product Features

- Improve levelling and slip for organic solvent system
- Prevent blocking for drying films
- Improve gloss for automotive coating system
- Improve DOI
- Superior anti- cratering

Application fields

- Acrylic urethane, acrylic air-drying system
- Acrylic, polyester high temperature baking system
- Solvent and solvent free based epoxy

Recommended dosage

- 0.1~0.4% on total formulation

Incorporation and Processing Instructions

- When it added let down process, Slip CFC-720P must be pre-mixing high speed

Packaging

- 15kg can, 160kg drum

The others

- Refer to the MSDS for toxicity and safe handling information.

CHEONGWOO CFC® CO.,LTD.

www.cfcadditive.com

Plant 1 : 14-1, Eogokgongdan-3gil, Yangsan-si, Gyeongnam, Korea(50591) TEL : 055-382-7576 FAX : 055-382-7584

Plant 2 : 80,Dasansandan-3gil, Dasanmyeon, Gyeongbuk, Korea (40113) TEL : 054-986-8441 FAX : 054-956-8440

※ Our information in document is based on our best knowledge. We disclaim any warranty and liability whatsoever as to accuracy and completeness of such information as well as to the potential infringement of any proprietary rights. We reserve the right to effect technical alterations. Any user of our products shall bear the full risk connected to their use including but not limited to their properties and fitness for any purpose.